



Single & Double-Ended LED Cordsets

Extended-life yellow LED – 100,000 hours continuous use
 Clear PVC body – female straight and 90°
 Provides output indication for AC sensors

NEW	3P with LED
FEMALE FACE VIEW	
COLOR CODE	1- green-gnd 3- red w/white-L1 2- red w/black-load red-L2
LED CIRCUIT DIAGRAM	
VOLTAGE	120V AC ± 10%
CURRENT	3A
CONDUCTOR	#18-4

FEMALE	FIG	SINGLE-ENDED CORDSETS WITH #18 AWG PVC CABLE 3 FEET LONG
STRAIGHT LED	1	1030A0A03F030
90° LED	2	1030A1A03F030
FEMALE/ MALE-4P	FIG	DOUBLE-ENDED CORDSETS WITH #18 AWG PVC CABLE 6 FEET LONG
STRAIGHT LED/ STRAIGHT	3	1130A2A03F060
90° LED/ STRAIGHT	4	1130A3A03F060
STRAIGHT LED/ 90°	5	1130A4A03F060
90° LED/ 90°	6	1130A5A03F060

CATALOG OPTIONS

Use the following chart to modify your part's specifications

1030A0A03F030

CABLE LENGTH

6'	060
12'	120
20'	200

Specifications



MECHANICAL	
CONNECTOR FACE:	PVC - UL STD 94 - V0
MOLDED BODY:	PVC - UL STD 94 - V0
COUPLING NUT:	ZINC DIECAST W/ BLACK EPOXY COAT
CABLE:	YELLOW, #18 AWG, PVC JACKET & PVC CONDUCTOR INSULATION OVER 41 X #34 COPPER STRANDING, 300V, UL STYLE Z661 CSA AWM III A/B 4P - .28" (7.1mm)
ELECTRICAL	
OUTSIDE DIAMETER:	300 V AC/DC
VOLTAGE RATING:	3P - 3A
AMPERAGE:	
ENVIRONMENTAL	
PROTECTION:	IP 68, NEMA 6P
AMBIENT OPERATING TEMP:	-4° to 221° F (-20° to 90° C)
CERTIFICATIONS	
UL:	UL RECOGNIZED, FILE NO. E46237
CSA:	CSA CERTIFIED, FILE NO. LR6837

CONNECTOR DIMENSIONS

