



# Double-Ended Cordsets

## Single Keyway M12

#18 AWG SJOOW cable – DC color code  
 Oil- and abrasion-resistant jacket  
 Highly reliable low-resistance contact design with gold/palladium nickel plating

	3P	4P
FEMALE FACE VIEW		
COLOR CODE	1- brown 2- not used 3- blue 4- black 5- not used	1- brown 2- white 3- blue 4- black 5- not used
VOLTAGE	250V AC/DC	250V AC/DC
CURRENT	4A	4A
CONDUCTOR	#18-3	#18-4

FEMALE/MALE	FIG	DOUBLE - ENDED CORDSETS WITH #18 AWG SJOOW CABLE 2 METERS LONG	
STRAIGHT/ STRAIGHT	1	883030C02M020	884030C02M020
90°/ STRAIGHT	2	883031C02M020	884031C02M020
STRAIGHT/ 90°	3	883032C02M020	884032C02M020
90°/90°	4	883033C02M020	884033C02M020

### CATALOG OPTIONS

Use the following chart to modify your part's specifications

883030C02M0201

**CABLE LENGTH**

4 METER	040
5 METER	050

**COUPLING NUT**

STAINLESS STEEL	ADD 1
-----------------	-------

# Specifications



<b>MECHANICAL</b>	
CONNECTOR FACE:	NYLON 6/6
MOLDED BODY:	PVC
O-RING:	NITRILE RUBBER
COUPLING NUT:	ZINC DIECAST W/ BLACK EPOXY COAT, OPTIONAL STAINLESS STEEL TYPE 303
CABLE:	YELLOW #18 AWG THERMOSET RUBBER JACKET AND EPDM CONDUCTOR INSULATION OVER 41 X #34 COPPER STRANDING, 300V, UL LISTED SJOW, CSA CERTIFIED SJOW
OUTSIDE DIAMETER:	3P - .32" (8.3mm) 4P - .33" (8.4mm)
<b>ELECTRICAL</b>	
VOLTAGE RATING:	250V AC/DC
AMPERAGE:	3P - 4A 4P - 4A
<b>ENVIRONMENTAL</b>	
PROTECTION:	IP 68, NEMA 6P
AMBIENT OPERATING TEMP:	-4° TO 221° F (-20° TO 105° C)
<b>CERTIFICATIONS</b>	
UL:	UL LISTED, FILE NO. E152210
CSA:	CSA CERTIFIED, FILE NO LR6837

## CONNECTOR DIMENSIONS

