



Double-Ended Cordsets

Single Keyway M12

#22 AWG yellow PVC cables with or without braid – DC color code
 Oil-resistant PVC jacket for all types of heavy-duty industrial environments
 Highly reliable low-resistance contact design with gold/palladium nickel plating


	3P	4P	5P
FEMALE FACE VIEW			
COLOR CODE	1- brown 2- not used 3- blue 4- black 5- not used	1- brown 2- white 3- blue 4- black 5- not used	1- brown 2- white 3- blue 4- black 5- gray
VOLTAGE	250V AC/DC	250V AC/DC	250V AC/DC
CURRENT	4A	4A	4A
CONDUCTOR	#22-3	#22-4	#22-5

FEMALE/MALE	FIG	DOUBLE-ENDED CORDSETS WITH #22 AWG PVC CABLE WITHOUT BRAID 2 METERS LONG		
STRAIGHT/STRAIGHT	1	883030A09M020	884030A09M020	885030A09M020
90°/STRAIGHT	2	883031A09M020	884031A09M020	885031A09M020
STRAIGHT/90°	3	883032A09M020	884032A09M020	885032A09M020
90°/90°	4	883033A09M020	884033A09M020	885033A09M020

CATALOG OPTIONS

Use the following chart to modify your part's specifications

883030A09M0201



Specifications



MECHANICAL	
CONNECTOR FACE:	NYLON 6/6
MOLDED BODY:	PVC
O-RING:	NITRILE RUBBER
COUPLING NUT:	ZINC DIECAST W/ BLACK EPOXY COAT, OPTIONAL STAINLESS STEEL TYPE 303
CABLE:	YELLOW #22 AWG PVC JACKET AND PVC CONDUCTOR INSULATION OVER 26 X #36 COPPER STRANDING, 300V, UL STYLE 2661, CSA I/II A/B, OPTIONAL 80% METALLIC BRAID
OUTSIDE DIAMETER:	<u>WITHOUT BRAID</u> <u>WITH BRAID</u> 3P - .18" (4.6mm) 3P - .23" (5.8mm) 4P - .20" (5.1mm) 4P - .25" (6.4mm) 5P - .23" (5.8mm) 5P - .26" (6.6mm)
ELECTRICAL	
VOLTAGE RATING:	250 V AC/DC
AMPERAGE:	3P - 4A 4P - 4A 5P - 4A
ENVIRONMENTAL	
PROTECTION:	IP 68, NEMA 6P
AMBIENT OPERATING TEMP:	-4° TO 221° F (-20° TO 105° C)
CERTIFICATIONS	
UL:	UL LISTED, FILE NO. E152210
CSA:	CSA CERTIFIED, FILE NO. LR6837

CONNECTOR DIMENSIONS

