

2P to 6P



Receptacles

360° Shield Dual Keyway 1/2" - 20 UNF

#22 AWG PVC 12-inch leads – AC color code, epoxy potted

Bright nickel-plated brass shell

For use with 360° shielded dual keyway cordsets

NEW	2P	3P	4P	5P	6P
MALE FACE VIEW					
COLOR CODE	1- brown 2- blue	1- green 2- red/black 3- red/white	1- red/black 3- red 2- red/white 4- green	1- red/white 4- red/yellow 2- red 5- red/black 3- green	1- red/white 4- red/yellow 2- red 5- red/black 3- green 6- red/blue
VOLTAGE	250V AC/DC	250V AC/DC	250V AC/DC	250V AC/DC	250V AC/DC
CURRENT	4A	4A	4A	4A	4A
CONDUCTOR	#22-2	#22-3	#22-4	#22-5	#22-6

TYPE	FIG	RECEPTACLES WITH #22 AWG PVC LEAD 12 INCHES LONG				
MALE 1/4-14NPT EXTERNAL THREADS	1	7R2006A19A1203	7R3006A19A1203	7R4006A19A1203	7R5006A19A1203	7R6006A19A1203

Specifications



MECHANICAL

SHELL: NICKEL-PLATED BRASS
 INSERT: NYLON 6/6
 O-RING: NITRILE RUBBER
 CONDUCTOR: #22 AWG WITH PVC INSULATION
 OVER 26 X #36 COPPER STRANDING,
 300V, UL STYLE 1061, CSA AWM SR

ELECTRICAL

VOLTAGE RATING: 250V AC/DC
 AMPERAGE: 2P TO 6P - 4A

ENVIRONMENTAL

PROTECTION: IP 68, NEMA 6P
 AMBIENT OPERATING TEMP: -4° TO 176° F (-20° TO 80° C)

CERTIFICATIONS

UL: UL LISTED, FILE NO. E152210
 CSA: CSA CERTIFIED, FILE NO LR6837

RECEPTACLE DIMENSIONS

